

LED Industrial - priemyselné svietidlá - Floodlight

Model	BN-TG2	BN-TG4
-------	---------------	---------------



Výkon	20W - 40W	50W - 120W
Svetelný tok	80 lm/W	80 lm/W
Rozmery mm/š x v	290x290x150	290x290x150
Váha	3900 g	4400 g
Vyžarovací uhol	30°-120°	30°-120°
Farba svetla	3000-7500 K	3000-7500 K
Napájanie	85-265VAC	85-265VAC
Pracovná teplota	-25°C~50°C	-25°C~50°C
CRI	Ra>80	Ra>80
Unit Efficiency	>90%	>90%
Krytie	IP67	IP67
Životnosť	50000 hod	50000 hod
Materiál	aluminum	aluminum

LED Industrial - priemyselné svetidlá - Floodlight

Model	AL-FL6W3	AL-FL12W3
-------	----------	-----------



Výkon	20W	40W
Svetelný tok	80 lm/W	80 lm/W
LED	HP 3W	HP 3W
Počet LED	6	12
Rozmery mm/š x v	280x210x180	280x210x180
Váha	3500 g	3500 g
Vyžarovací uhol	15° 90°	15° 90°
Farba svetla	WW/DW/R/G/B/Y	WW/DW/R/G/B/Y
Napájanie	100-240VAC	100-240VAC
Pracovná teplota	-25°C ~ 50°C	-25°C ~ 50°C
CRI	Ra>80	Ra>80
Unit Efficiency	>90%	>90%
Krytie	IP65	IP65
Životnosť	50000 hod	50000 hod
Materiál	aluminum	aluminum

LED Industrial - priemyselné svietidlá - Floodlight

Model	AL-FL36W1	AL-FL48W1
-------	-----------	-----------



Výkon	50W	70W
Svetelný tok	80 lm/W	80 lm/W
LED	HP 1W	HP 1W
Počet LED	36	48
Rozmery mm/š x v	394x437x280	394x437x280
Váha	7200 g	8200 g
Vyžarovací uhol	15° 90°	15° 90°
Farba svetla	WW/DW/R/G/B/Y	WW/DW/R/G/B/Y
Napájanie	100-240VAC	100-240VAC
Pracovná teplota	-25°C ~ 50°C	-25°C ~ 50°C
CRI	Ra>80	Ra>80
Unit Efficiency	>90%	>90%
Krytie	IP65	IP65
Životnosť	50000 hod	50000 hod
Materiál	aluminum	aluminum
Poznámka	verzie RGB ovládané DMX512	